VALUE • INTEGRITY • PERFORMANCE

SVP SERIES

Wharfedale Pro

FEATURES OF THE SVP SERIES:

- 1" FERROFLUID COMPRESSION DRIVER
- ELLIPTICAL WAVEGUIDE TECHNOLOGY, PROVIDES SUPERIOR CONTROL, GREATER OUTPUT CAPABILITY & NATURAL, OPEN, LOW DISTORTION HIGH FREQUENCY REPRODUCTION
- TRAPEZOIDAL ENCLOSURES FOR EASY ARRAY & SONIC ACCURACY
- PRO-TECH™ DRIVER PROTECTION SYSTEM
- DURABLE BLACK CARPET COVERING
- RUGGED PROTECTIVE STEEL CORNERS & GRILLS
- INTEGRAL HANDLES
- METAL POLE STAND ADAPTOR
- TWO 1/4" JACK SOCKETS
- LOW RESONANCE ENCLOSURE DESIGN

SVP12

WWW.WHARFEDALEPRO.COM

Wharfedale Pro is a member of the International Audio Group (IAG)

IAG

VALUE - INTEGRITY - PERFORMANCE

SVP SPECIFICATIONS

SVP12

MODEL	SVP10	SVP12	SVP12M	SVP15	SVP215	SVP15B	SVP18B
FREQUENCY RESPONSE							
@+/- 3dB	65-20kHz	50-20kHz	50-20kHz	45-20kHz	40-20kHz	45-250Hz	40-250Hz
COVERAGE (H x V)	90°x 60	90°x 60	90°x 60	90°x 60	90°x 60	--	--
POWER HANDLING (watts)							
Continuous	100	150	150	200	250	250	300
Music	200	300	300	400	500	500	600
Peak	400	600	600	800	1000	1000	1200
SENSITIVITY 1w@1m(dB)	96	97	97	98	101	98	99
PEAK SPL (dB)	121.5	124.5	124.5	126	129.5	126.5	129.5
SYSTEM IMPEDANCE (Ω)	8	8	8	8	4	8	8
LF DRIVER							
Driver size	10"	12"	12"	15"	15"	15"	18"
Coil size(mm/ins)	39/1.5"	51/2"	51/2"	51/2"	38/1.5"	65/2.5"	75/3"
HF SECTION							
Coil size(mm/ins)	25/1"	25/1"	25/1"	25/1"	25/1"	--	--
Exit size(mm/ins)	30/1.2"	30/1.2"	30/1.2"	30/1.2"	30/1.2"	--	--
HF protection	Bulb	Bulb	Bulb	Bulb	Bulb	--	--
HF HORN	Elliptical	Elliptical	Elliptical	Elliptical	Elliptical	--	--
CROSSOVER SECTION							
Crossover Frequency	3.2k	3.2k	3.2k	3.2k	3.2k	150Hz/6dB	150Hz/6dB
High Pass Output	--	--	--	--	--	150Hz/6dB	150Hz/6dB
ENCLOSURE TYPE							
Shape	Trapezoid	Trapezoid	Floor monitor	Trapezoid	Trapezoid	Rectangular	Rectangular
Finish colour	Carpet black	Carpet black	Carpet black	Carpet black	Carpet black	Carpet black	Carpet black
Stand adaptor	Yes	Yes	No	No	No	Yes	Yes
Protect corner	Black metal	Black metal	Black metal	Black metal	Black metal	Black metal	Black metal
Handle	2	2	2	2	2	2	2
Type	Teardrop	Teardrop	Teardrop	Teardrop	Teardrop	Teardrop	Teardrop
INPUT CONNECTOR	1/4" phonex2	1/4" phonex2	1/4" phonex2	1/4" phonex2	1/4" phonex2	1/4" phonex2	1/4" phonex2
HIGH PASS OUT	No	No	No	No	No	1/4" phone	1/4" phone
DIMENSIONS							
Height (mm)	494	554	415	638	1014	587	748
Width (mm)	317	428	428	463	463	548	548
Depth (mm)	288	355	554	390	390	429	450
WEIGHT (kg)	10.28	15.58	14.9	19.26	31.0	31.52	38.56

Wharfedale Pro

Wharfedale International Ltd. IAG House, Sovereign Court, Ermine Business Park, Huntingdon, Cambs, PE29 6XU.
Tel: +44 (0) 1480 447700 Fax: +44 (0) 1480 431767 Email: sales@wharfedalepro.com

WWW.WHARFEDALEPRO.COM

Wharfedale Pro is a member of the International Audio Group (IAG)
The information in this brochure is subject to change without notice
All rights reserved © 2004 Wharfedale Pro

IAG
International Audio Group